



# Floor-to-Ceiling Restroom Partitions

## No-Site Bradmar® Solid Plastic (HDPE) — Series 700

This style of partitions is similar to our standard series 700 partitions with an added "No-Site" feature. The feature consists of matching profiles on the hinge side and an overlap on the strike side to prevent a line of sight. It is mounted to the floor and ceiling and recommended where additional stability is desired. Applicable for ceiling heights up to 10'. (Partitions must be installed in a climate-controlled environment, away from direct sunlight.)

### Construction

Doors, panels and pilasters are constructed from 1" thick High Density Polyethylene (HDPE) resins pressed under high pressure to form a single component. This material is waterproof, non-absorbent and has a self-lubricating surface which resists marks from graffiti. All plastic components are shipped with a self-adhesive coating for protection during installation. Bradmar® is available in a variety of colors.

### Panels and Doors

Panels and doors are fabricated 55" high, all edges are rounded to a 3/16" radius. Panels and doors receive an aluminum heat sink strip which helps dissipate any applied heat. Each door is pre-drilled to receive an integral hinge assembly. The closing position of each hinge is fully adjustable.

### Pilasters

Pilasters are secured through the face of the shoe using Torx-head thru-bolts. 5/16" lag screw(s) (provided in shoe kit) can be added to the floor edge of the pilaster for leveling. The ceiling edge of the pilaster shall be connected to the ceiling using L-type brackets and Torx-head screws.

### Hardware

Bradley standard hardware is constructed from 6463-T5 heavy-duty aluminum. Compartments are provided with all hardware and stainless steel torx head w/ pin fasteners to complete installation for applications with concrete floors and masonry block walls.

### Door Hardware

Standard integral hinge system consisting of a 1/2" diameter nylon gravity cam unit with a 3/16" stainless steel center pin (bottom) and a 1/2" nylon rod (top). Keeper is 2 1/2" long and is fabricated from heavy-duty extruded aluminum (6063 alloy). No strike hardware is required because the overlap feature acts as a door stop. Latches shall be fabricated from heavy-duty extruded aluminum (6463-T5 alloy). Slide bolt shall have a black anodized finish. Latch is mounted to the door with stainless steel theft-resistant screws. The slide latch does not require a twisting motion and complies with all Federal ADA guidelines. Keeper is mounted to the pilaster with thru-bolts. Coat hooks, door bumpers and door pulls are provided in Zamac material with satin finish. Outswing doors are supplied with an individual coat hook, door bumper, and double door pull. Inswing ADA doors are also supplied with a double door pull. Theft-resistant fasteners are supplied with all hardware.

### Brackets

Continuous brackets are fabricated from heavy-duty aluminum (6463-T5), are 54" long and are available in single-, double-, or no ear ("U") style.

### Shoes and Sleeves

Shoes are 1-piece, 4" high, 300 Series stainless steel with #4 satin finish and are secured to the floor with Torx-head screws. Sleeves of the same material are secured to the face of the pilaster using Torx-head screws.



### Standard Selections (Must select one from each category)

#### Partition Colors

**NOTE: Click on any swatch to view as a larger image.**

- Canyon Granite
- Charcoal Gray
- Deep Blue
- Desert Stone
- Starry Night

#### Door Hardware

- Aluminum (STD)
- Stainless Steel

#### Hinge

- Integral (STD)

#### Wall Brackets

- Continuous – Aluminum (STD)
- Continuous – Stainless Steel
- Stirrup Style – Aluminum

### Optional Selections

#### Extra Height

- 69"/72" H Doors and Panels <sup>1</sup>

#### Miscellaneous

- Cutouts

<sup>1</sup> ADA stalls will have 69"H doors and panels, 9" AFF. All other stalls in the room will be 72"H/6" AFF to allow for maximum privacy.



Verify all rough-in dimensions prior to installation.

Consult local and national codes. Conformity and compliance to local and national codes is the responsibility of the installer.

Page 1 of 1 1/26/2024

This information is subject to change without notice.

Bradley\_Partitions\_Bradmar\_NoSiteFloorToCeiling

[View Latest Version](#)

Bradley Partitions are protected by the following U.S. Patents:  
D613,882; D623,769S; 7,987,635

© 2024 Bradley  
P.O. Box 309, Menomonee Falls, WI 53052-0309  
800 BRADLEY (800 272 3539) +1 262 251 6000  
bradleycorp.com